



# Certificate of Compliance

**Certificate:** 70137092

**Master Contract:** 155068

**Project:** 70137092

**Date Issued:** 2017-06-28

**Issued to:** Philips Lighting Electronics N.A.  
O'Hare International Center  
10275 W. Higgins Rd.  
ROSEMONT, IL 60018-560  
U.S.A.

**Attention:** Mr. Ernesto Mendoza

*The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US (indicating that products have been manufactured to the requirements of both Canadian and US Standards) or with adjacent indicator 'US' for US only or without either indicator for Canada only*



**Issued by:**

Robin Huang

## **PRODUCTS**

CLASS 3426 32 - LUMINAIRES - LED Drivers

CLASS 3426 92 - LUMINAIRES - LED Drivers - Certified to US Standards

LED Driver, suitable for wet location, enclosed and fully potted, Inherently Limited, Isolated Non-Class 2 output.

Model 9290014087, Input rated 110-277 V ac, 50/60Hz, 0.42-0.18 A ac, Output rated 35-57 V dc, 0.7 A dc, maximum output voltage 80V dc.

Model 9290014088, Input rated 110-277 V ac, 50/60Hz, 0.27-0.12 A ac, Output rated 20-36 V dc, 0.7 A dc, maximum output voltage 50V dc.

## **Notes:**

1. The above devices are for use in other equipment, where the acceptability of the final combination is to be determined by CSA or other NRTL.



**Certificate:** 70137092

**Master Contract:** 155068

**Project:** 70137092

**Date Issued:** 2017-06-28

## CONDITIONS OF ACCEPTABILITY

When installed in the end-use equipment, the following are among the considerations to be made:

1. These products are for use only in (or with) complete end product equipment where the acceptability of the combination is determined by CSA International or others having jurisdiction.
2. The product shall be installed in compliance with the enclosure, mounting, mounting surface, spacing, and segregation requirements of the End Product in which it is employed. Suitability shall be determined during End Product Certification Evaluation.
3. This product has been evaluated for use in “DRY, DAMP AND WET LOCATION”.
4. This product was evaluated for use within the parameters of its marked ratings. In the final application, the enclosure temperature shall be within the marking rating - maximum enclosure (case) temperature Tc of 80 °C for 9290014087 and maximum enclosure (case) temperature Tc of 75 °C for 9290014088.

### 5. Wiring:

<i>Cord with three wires inside (Input)</i>		
Brown	Blue	Green/Yellow
Line	Neutral	Grounding (EMC improvement)
<i>Cord with two wires inside (Output)</i>		
Blue	Brown	/
LED +	LED -	/

## APPLICABLE REQUIREMENTS

UL8750, 1<sup>st</sup> Ed – Light Emitting Diode (LED) Equipment for Use in Lighting Products.

CAN/CSA-C22.2 No. 250.13-14 – Light emitting diode (LED) equipment for lighting applications



## *Supplement to Certificate of Compliance*

**Certificate:** 70137092

**Master Contract:** 155068

*The products listed, including the latest revision described below,  
are eligible to be marked in accordance with the referenced Certificate.*

### **Product Certification History**

---

<b>Project</b>	<b>Date</b>	<b>Description</b>
70137092	2017-06-28	Original Certification