

CERTIFICATE

Issued to:
Applicant:
Signify Netherlands B.V.
High Tech Campus 48
5656 AE Eindhoven, The Netherlands

Licensee:
Signify Netherlands B.V.
High Tech Campus 48
5656 AE Eindhoven, The Netherlands

Product : LED driver
Trade name(s) : PHILIPS
Type(s)/model(s) : Xitanium 35W 0.08-0.35A 150V S 230V, Xitanium 60W 0.08-0.35A 220V S 230V
and Xitanium 60W 0.08-0.35A 300V S 230V

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard EN 61347-1:2015, EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 62384:2006 and EN 62384:2006/A1:2009
- an inspection of the production location according to CENELEC Operational Document CIG 021
- a certification agreement with the number 947556

DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration of the ENEC certification agreement and under the conditions of the ENEC certification agreement.

This certificate is issued on 12 March 2020 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 31-108120 REV.1

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



H.R.M. Barends
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: LED driver
Trade name(s)	: PHILIPS
Type(s)/model(s)	: Xitanium 35W 0.08-0.35A 150V S 230V, Xitanium 60W 0.08-0.35A 220V S 230V and Xitanium 60W 0.08-0.35A 300V S 230V
Rated input voltage	: 220-240 Vac/Vdc
Rated frequency	: 50/60 Hz at ac
Output current	: 0,08-0,35 A
Mac. case temperature (tc)	: 75 °C
Ambient temperature range(ta)	: -25...+50 °C
Power factor (pf)	: 0,9C
Temperature declared thermally protection	: 110 °C
Description	: Built-in

Product data – type Xitanium 35W 0.08-0.35A 150V S 230V

Rated input current	: 0,17 A
Rated input power	: 39 W
Output voltage	: 50-150 V; 250 V max.
Output power	: 35 W

Product data – type Xitanium 60W 0.08-0.35A 220V S 230V

Rated input current	: 0,3 A
Rated input power	: 66 W
Output voltage	: 50-220 V; 250 V max.
Output power	: 60 W

Product data – type Xitanium 60W 0.08-0.35A 300V S 230V

Rated input current	: 0,3 A
Rated input power	: 66 W
Output voltage	: 100-300 V; 330 V max.
Output power	: 60 W

TESTS**Test requirements**

EN 61347-1:2015
EN 61347-2-13:2014
EN 61347-2-13:2014/A1:2017
EN 62384:2006
EN 62384:2006/A1:2009

Test result

The test results are laid down in DEKRA test file 605057100.

Additional information

- constant current is set by means of NFC
- suitable for emergency lighting luminaire acc. IEC 60598-2-22. excluding high risk task areas.

The tests were performed by the manufacturer under the conditions of the agreement concerning the manufacturer's right to conduct type tests for the KEMA-KEUR / ENEC certification system under supervision of DEKRA (CTF Stage 3).

This certificate replaces certificate No. 31-108120 which we hereby declare invalid.

The list of components is laid down at test report 6050571.50.

Conclusion

The examination proved that all requirements were met.

Factory locations

The factory locations are registered with the numbers 674666, 305810 and 326285.