

# IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

|  |   |
|--|---|
| Product  | LED driver  |
| Name and address of the applicant                                    | Philips Lighting B.V.<br>High Tech Campus 45, 5656 AE Eindhoven<br>The Netherlands  |
| Name and address of the manufacturer                                 | Philips Lighting B.V.<br>High Tech Campus 45, 5656 AE Eindhoven<br>The Netherlands  |
| Name and address of the factory                                      | <input checked="" type="checkbox"/> Additional information on page 2<br>Taiwan Surface Mounting Technology (SuZhou) Co., Ltd.<br>No. 888 Ganquan Dong Road, Economic Technology Development Zone, Wujiang, Suzhou<br>China  |
| Note: When more than one factory, please report on page 2            |   |
| Ratings and principal characteristics                                | <p>Xi FP 22W 0.2-0.7A SNLDAE 230V S175 sXt:<br/>Uin: 220-240 V; fn: 50/60 Hz; lin: 0,12-0,11 A; Pin: 26 W; PF: 0,95;<br/>Iout: 200-700 mA; Pout: 22 W; Uout: 16-48 Vdc, 70 Vmax;<br/>ta: -40...+55 °C; tc: 85 °C; Built-in; SELV</p> <p>Xi FP 22W 0.3-1.0A SNLDAE 230V S175 sXt:<br/>Uin: 220-240 V; fn: 50/60 Hz; lin: 0,12-0,11 A; Pin: 26 W; PF: 0,95;<br/>Iout: 300-1050 mA; Pout: 22 W; Uout: 8-32 Vdc, 50 Vmax;<br/>ta: -40...+55 °C; tc: 85 °C; Built-in; SELV</p> <p>Xi FP 40W 0.2-0.7A SNLDAE 230V S175 sXt:<br/>Uin: 220-240 V; fn: 50/60 Hz; lin: 0,21-0,19 A; Pin: 46 W; PF: 0,95;<br/>Iout: 200-700 mA; Pout: 40 W; Uout: 25-77 Vdc, 100 Vmax;<br/>ta: -40...+55 °C; tc: 85 °C; Built-in; SELV</p> <p>Xi FP 40W 0.3-1.0A SNLDAE 230V S175 sXt:<br/>Uin: 220-240 V; fn: 50/60 Hz; lin: 0,21-0,19 A; Pin: 46 W; PF: 0,95;<br/>Iout: 300-1050 mA; Pout: 40 W; Uout: 20-54 Vdc, 60 Vmax;<br/>ta: -40...+55 °C; tc: 90 °C; Built-in; SELV</p> |
| Trademark (if any)   | PHILIPS   |
| Customer's Testing Facility (CTF) Stage used                         | CTF Stage 3   |
| Model / Type Ref.  | Xi FP 22W 0.2-0.7A SNLDAE 230V S175 sXt<br>Xi FP 22W 0.3-1.0A SNLDAE 230V S175 sXt<br>Xi FP 40W 0.2-0.7A SNLDAE 230V S175 sXt<br>Xi FP 40W 0.3-1.0A SNLDAE 230V S175 sXt  |
| Additional information (if necessary may also be reported on page 2) | <input type="checkbox"/> Additional information on page 2   |

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.  
Meander 1051, NL-6825 MJ Arnhem, Netherlands



IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

A sample of the product was tested and found  
to be in conformity with

IEC 61347-1:2015, IEC 61347-2-13:2014, IEC 61347-2-13:2014/AMD1:2016

National differences:

EU Group Differences

6018495.50

As shown in the Test Report Ref. No. which  
forms part of this Certificate

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.  
Meander 1051, NL-6825 MJ Arnhem, Netherlands



IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

**Additional factory**

Philips Lighting Electronics Poland  
ul Przemysłowa 29, 64-920 Pila  
Poland

Fideltronik Poland Sp.z.o.o.  
ul Beniowskiego 1, 34-200, SUCHA BESKIDZKA  
Poland

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.  
Meander 1051, NL-6825 MJ Arnhem, Netherlands

