

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME**
CB TEST CERTIFICATE

Product

Built-in LED Module

Name and address of the applicant

Signify Netherlands B.V.
High Tech Campus 48
Eindhoven, 5656 AE Netherlands

Name and address of the manufacturer

Signify Netherlands B.V.
High Tech Campus 48
Eindhoven, 5656 AE Netherlands

Name and address of the factory

Note: When more than one factory, please report on page 2

☒ Additional Information on page 2

Ratings and principal characteristics

Imax 2750 mA DC Vmax 44 V DC
(see Page 2-6 for further ratings)

Trademark / Brand (if any)

PHILIPS

Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Main series: **Fortimo SLM C zcc dd m Lee s G i a**
(see Page 2-6 for Product Key explanation and variant series)

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to: EN 62031:2008/ A1:2013 / A2:2015
National differences specified in the CB Test Report

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62031:2008/AMD1:2012, IEC 62031:2008/AMD2:2014,
IEC 62031:2008

As shown in the Test Report Ref. No. which forms part of this Certificate

4789288222-1 issued on 2019-12-11

This CB Test Certificate is issued by the National Certification Body


UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:

Jan-Erik Storgaard

Factories:

Model Details:

Product Key:

Main series: **Fortimo SLM C zcc dd m Lee s Gi a**

Where:

- z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 25 and 57);
dd = Color of light (two or three characters or none, may be "CW" or "FP" or "FPR" or "FW" or "FWW" or "PW" or blank)
m = Die matrix (4 digits, may be "1202" or "1203" or "1204" or "1205" or "1208" or "1211")
ee = Diameter of Light Emitting Surface (LES) in mm (one or two digits, may be a value between 9 and 19);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm));
i = Number of generation of CoB (one digit, may be "4" or "5");
a = Suffix for commercial purposes (optional)

Maximum ratings of the series:

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	tc [°C]
1211	19	≤ 4000	2400 (V _{f tot} 37,5 V)	90	0,32	105
		> 4000	1500 (V _{f tot} 36 V) *	54	0,19	
1208	15	≤ 4000	1690 (V _{f tot} 36 V)	60,8	0,34	105
		> 4000	935 (V _{f tot} 36 V) *	33,7	0,19	
1205	13	≤ 4000	1200 (V _{f tot} 36 V)	43,2	0,33	105
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19	
1204	13	≤ 4000	960 (V _{f tot} 36 V)	34,6	0,26	105
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19	
1203	9	≤ 4000	600 (V _{f tot} 36 V)	21,6	0,34	105
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19	
1202	9	≤ 4000	480 (V _{f tot} 36 V)	17,3	0,27	105
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19	

*: See additional information

Higher numeric generations of CoB is suitable replacement for lower numeric generations without additional normal temperature test on final product if:

- The final product thermal management construction is not reduced, and
- The CoB size is identical, and
- The rated power of CoB is lower or equal.

Additional information (if necessary)


UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:

Jan-Erik Storgaard

Variants:

Product Key:

Variant series 1: **Fortimo SLM** zcc Lee hh s Gij a

Where:

- z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 25 and 57);
ee = Diameter of Light Emitting Surface (LES) in mm (one or two digits, may be a value between 9 and 19);
hh = Holder type (two characters or none, may be "DL" or "PI" or "ZP" or "ZPw" or blank);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm));
l = Number of generation of CoB (one digit, may be "4" or "5");
j = Number of generation of Holder (one digit, may be "1" or "2");
a = Suffix for commercial purposes (optional)

The variant series 1 differs from the main series for different product key and for the presence of LED CoB + LED Holder.

Maximum ratings of the series:

CoB Type	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density of CoB [W/ mm ²]	tc [°C]	T Holder [°C]
1211	19	≤ 4000	2400 (V _{f tot} 37,5 V)	90	0,32	105	100
		> 4000	1500 (V _{f tot} 36 V) *	54	0,19		
1208	15	≤ 4000	1690 (V _{f tot} 36 V)	60,8	0,34	105	100
		> 4000	935 (V _{f tot} 36 V) *	33,7	0,19		
1205	13	≤ 4000	1200 (V _{f tot} 36 V)	43,2	0,33	105	100
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19		
1204	13	≤ 4000	960 (V _{f tot} 36 V)	34,6	0,26	105	100
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19		
1203	9	≤ 4000	600 (V _{f tot} 36 V)	21,6	0,34	105	100
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19		

1202	9	≤ 4000	480 (V _{f tot} 36 V)	17,3	0,27	105	100
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19		

* : See additional information

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:



Jan-Erik Storgaard

Product Key:

Variant series 2: **Fortimo SLM C zcc dd m Lee s Gi a**

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 22 and 65);
dd = Color of light (two or three characters or none, may be "CW" or "FPR" or "FWW" or "PW" or "PC" or "FLS" or "FIS" or "FVF" or blank)
m = Die matrix (4 digits, may be "1202" or "1203" or "1204" or "1205" or "1206" or "1208" or "1211" or "1216")
ee = Diameter of Light Emitting Surface (LES) in mm (two digits, may be a value between 06 and 23);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm);
i = Number of generation of CoB (one digit, may be "6", "7");
a = Suffix for commercial purposes (optional)

Maximum ratings of the series:

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]
1216	23 *	2750 (V _{f tot} 41 V)	113	0,27	105
1211	18.5*	2400 (V _{f tot} 41 V)	98	0,37	105
1208	15 *	1710 (V _{f tot} 41 V)	70	0,40	105
1206	13 *	1200 (V _{f tot} 41 V)	49	0,37	105
1205	13 *	1050 (V _{f tot} 41 V)	43	0,32	105
1204	13 ^	850 (V _{f tot} 41 V)	35	0,26	105
	9 **	1350 (V _{f tot} 44 V)	59	0,93	105
	9 ^	740 (V _{f tot} 41 V)	30	0,48	105
1203	9 *	570 (V _{f tot} 41 V)	23	0,37	105
1202	6,5 ^	380 (V _{f tot} 41 V)	16	0,47	105
	6 **	675 (V _{f tot} 44 V)	30	0,90	105

^: Concerning CoB's Generation 6

*: Concerning CoB's Generation 6 and 7

**: Concerning CoB's Generation 7

Additional information (if necessary)


UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:



Jan-Erik Storgaard

Product Key:

Variant series 3: **Fortimo SLM zcc Lee hh s Gij a**

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 22 and 65);
ee = Diameter of Light Emitting Surface (LES) in mm (two digits, may be a value between 06 and 23);
hh = Holder type (two or three characters or none, may be "DL" or "PI" or "ZP" or "ZPw" or blank);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm);
i = Number of generation of CoB (one digit, may be "6", "7");
j = Number of generation of Holder (one digit, may be "1" or "2");
a = Suffix for commercial purposes (optional)

The variant series 3 differs from the variant series 2 for different product key, for the presence of LED CoB + LED Holder and for different maximum ratings for CoB Type 1216.

Maximum ratings of the series:

CoB Type	Diameter of LES of CoB [mm]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]	T Holder [°C]
1216	23 *	2750 (V _{f tot} 41 V)	98	0,27	105	100
1211	18.5*	2400 (V _{f tot} 41 V)	98	0,37	105	100
1208	15 *	1710 (V _{f tot} 41 V)	70	0,40	105	100
1206	13 *	1200 (V _{f tot} 41 V)	49	0,37	105	100
1205	13 *	1050 (V _{f tot} 41 V)	43	0,32	105	100
1204	13 ^	850 (V _{f tot} 41 V)	35	0,26	105	100
	9 **	1350 (V _{f tot} 44 V)	59	0,93	105	100
	9 ^	740 (V _{f tot} 41 V)	30	0,48	105	100
1203	9 *	570 (V _{f tot} 41 V)	23	0,37	105	100
1202	6,5 ^	380 (V _{f tot} 41 V)	16	0,47	105	100
	6 **	675 (V _{f tot} 44 V)	30	0,90	105	100

^: Concerning CoB's Generation 6

*: Concerning CoB's Generation 6 and 7

**: Concerning CoB's Generation 7

Additional information (if necessary)


UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:



Jan-Erik Storgaard

Additional information:

- The modules have been evaluated according to IEC/TR 62778 and the Lamp classification Group for Blue Light Hazard is Risk Group 1 Unlimited for modules having generation of CoB "4" or "5", Risk Group 2 for modules having generation of CoB "6", "7" when are used at maximum rated currents. These Generation 6, 7 modules are classified as Risk Group 1 if they are used according to the maximum currents listed below:

-	CoB Type							
	1216	1211	1208	1205	1204	1204s	1203	1202s
Maximum Currents for RG1 Classif. [mA]	1824 (Gen 6)	1254 (Gen 6)	912 (Gen 6)	570 (Gen 6)	456 (Gen 6)	456	342 (Gen 6)	228

-		CoB Type							
		1216	1211	1208	1206	1205	1204	1203	1202
Maximum Currents for RG1 Classif. [mA]	zcc = 765	1797 (Gen 7)	1248 (Gen 7)	548 (Gen 7)	/	468 (Gen 7)	/	258 (Gen 7)	/
	zcc = 857	2298 (Gen 7)	1349 (Gen 7)	1040 (Gen 7)	1000 (Gen7)	820 (Gen 7)	480 (Gen 7)	330 (Gen 7)	157 (Gen7)

Additional information (if necessary)

☐ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

☒ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

☐ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

☐ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-12-11

Signature:



Jan-Erik Storgaard