

ENEC LICENSE

License No. ENEC-01182-P5
Page 1/8
Date of Issue 2019-12-11

License Holder Signify Netherlands B.V.
High Tech Campus 48
Eindhoven, 5656 AE Netherlands
Production site

Certification Mark See Annex 1
Certified Product Built-in LED Module
Model Main series: **Fortimo SLM C zcc dd m Lee s Gi a**
See Page 3-8 for Product Key explanation and variant series

Trademark **PHILIPS**

Rated Voltage / Frequency Vmax 44 V DC
Rated Current / Power Imax 2750 mA DC
Insulation Class --
Degree of protection (IP) --
Tested acc. to EN 62031:2008/A1:2013, EN 62031:2008/A2:2015, EN 62031:2008
Test Report No. 4789288222-1 issued on 2019-12-11
Additional See page 2

Certification Manager
Jan-Erik Storgaard

Certification Body

This is to certify that representative sample(s) of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this License, in accordance with the ENEC Requirements. The Designated License holder is entitled to use the ENEC 15 Mark (as shown in annex 1) for the Certified Product manufactured at the production site(s) identified above in accordance with the ENEC Mark Service Agreement including without limitation the ENEC Mark Testing and Certification Services Service Terms. Only those Products bearing the ENEC Mark should be considered as being covered by UL's ENEC Mark Service. This License shall remain valid unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the Date of Withdrawal of conflicting Standard(s).

UL International Demko A/S, Borupvang 5A, DK-2750
Ballerup, Denmark, Tel. +45 44 85 65 65, info.dk@ul.com
www.ul-europe.com



ENEC LICENSE

License No.	ENEC-01182-P5
Page	2/8
Date of Issue	2019-12-11

Production Sites:

Additional Information:

This certificate replaces the earlier issued ENEC-01182-P4 dated 2019-08-27.

Certification Body

This is to certify that representative sample(s) of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this License, in accordance with the ENEC Requirements. The Designated License holder is entitled to use the ENEC 15 Mark (as shown in annex 1) for the Certified Product manufactured at the production site(s) identified above in accordance with the ENEC Mark Service Agreement including without limitation the ENEC Mark Testing and Certification Services Service Terms. Only those Products bearing the ENEC Mark should be considered as being covered by UL's ENEC Mark Service. This License shall remain valid unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the Date of Withdrawal of conflicting Standard(s).



ENEC LICENCE

Licence No. ENEC-01182-P5
Page 3/8
Date of Issue 2019-12-11

Model Details:

Product Key:

Main series: **Fortimo SLM C zcc dd m Lee s Gi a**

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 25 and 57);
dd = Color of light (two or three characters or none, may be "CW" or "FP" or "FPR" or "FW" or "FWW" or "PW" or blank)
m = Die matrix (4 digits, may be "1202" or "1203" or "1204" or "1205" or "1208" or "1211")
ee = Diameter of Light Emitting Surface (LES) in mm (one or two digits, may be a value between 9 and 19);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm));
i = Number of generation of CoB (one digit, may be "4" or "5");
a = Suffix for commercial purposes (optional)

Maximum ratings of the series:

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]
1211	19	≤ 4000	2400 (V _{f tot} 37,5 V)	90	0,32	105
		> 4000	1500 (V _{f tot} 36 V) *	54	0,19	
1208	15	≤ 4000	1690 (V _{f tot} 36 V)	60,8	0,34	105
		> 4000	935 (V _{f tot} 36 V) *	33,7	0,19	
1205	13	≤ 4000	1200 (V _{f tot} 36 V)	43,2	0,33	105
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19	
1204	13	≤ 4000	960 (V _{f tot} 36 V)	34,6	0,26	105
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19	
1203	9	≤ 4000	600 (V _{f tot} 36 V)	21,6	0,34	105
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19	
1202	9	≤ 4000	480 (V _{f tot} 36 V)	17,3	0,27	105
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19	
* : See additional information						

Higher numeric generations of CoB is suitable replacement for lower numeric generations without additional normal temperature test on final product if:

- The final product thermal management construction is not reduced, and
- The CoB size is identical, and
- The rated power of CoB is lower or equal.

The product and production sites listed on the License comply with the ENEC requirement and the UL Global Service Agreement, with reference to Terms and Conditions for the ENEC mark. The Owner of the License is entitled to use the ENEC 15 (as shown in annex 1) for the products listed on the License and manufactured at the production site listed. UL has to be informed in writing about any changes to the product or production site in accordance with the Term and Conditions of the ENEC mark.



ENEC LICENCE

Licence No. ENEC-01182-P5
 Page 4/8
 Date of Issue 2019-12-11

Variants:

Product Key:

Variant series 1: **Fortimo SLM** zcc Lee hh s Gij a

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
 cc = Color temperature of LED divided by 100 (two digits, may be a value between 25 and 57);
 ee = Diameter of Light Emitting Surface (LES) in mm (one or two digits, may be a value between 9 and 19);
 hh = Holder type (two characters or none, may be "DL" or "PI" or "ZP" or "ZPw" or blank);
 s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm);
 i = Number of generation of CoB (one digit, may be "4" or "5");
 j = Number of generation of Holder (one digit, may be "1" or "2");
 a = Suffix for commercial purposes (optional)

The variant series 1 differs from the main series for different product key and for the presence of LED CoB + LED Holder.

Maximum ratings of the series:

CoB Type	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]	T Holder [°C]
1211	19	≤ 4000	2400 (V _{f tot} 37,5 V)	90	0,32	105	100
		> 4000	1500 (V _{f tot} 36 V) *	54	0,19		
1208	15	≤ 4000	1690 (V _{f tot} 36 V)	60,8	0,34	105	100
		> 4000	935 (V _{f tot} 36 V) *	33,7	0,19		
1205	13	≤ 4000	1200 (V _{f tot} 36 V)	43,2	0,33	105	100
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19		
1204	13	≤ 4000	960 (V _{f tot} 36 V)	34,6	0,26	105	100
		> 4000	700 (V _{f tot} 36 V) *	25,2	0,19		
1203	9	≤ 4000	600 (V _{f tot} 36 V)	21,6	0,34	105	100
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19		
1202	9	≤ 4000	480 (V _{f tot} 36 V)	17,3	0,27	105	100
		> 4000	340 (V _{f tot} 36 V) *	12,2	0,19		

* : See additional information

The product and production sites listed on the License comply with the ENEC requirement and the UL Global Service Agreement, with reference to Terms and Conditions for the ENEC mark. The Owner of the License is entitled to use the ENEC 15 (as shown in annex 1) for the products listed on the License and manufactured at the production site listed. UL has to be informed in writing about any changes to the product or production site in accordance with the Term and Conditions of the ENEC mark.



ENEC LICENCE

Licence No. ENEC-01182-P5
 Page 5/8
 Date of Issue 2019-12-11

Product Key:

Variant series 2: **Fortimo SLM C zcc dd m Lee s Gi a**

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
 cc = Color temperature of LED divided by 100 (two digits, may be a value between 22 and 65);
 dd = Color of light (two or three characters or none, may be "CW" or "FPR" or "FWW" or "PW" or "PC" or "FLS" or "FIS" or "FVF" or blank)
 m = Die matrix (4 digits, may be "1202" or "1203" or "1204" or "1205" or "1206" or "1208" or "1211" or "1216")
 ee = Diameter of Light Emitting Surface (LES) in mm (two digits, may be a value between 06 and 23);
 s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm);
 i = Number of generation of CoB (one digit, may be "6", "7");
 a = Suffix for commercial purposes (optional)

Maximum ratings of the series:

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]
1216	23 *	2750 (V _{f tot} 41 V)	113	0,27	105
1211	18.5*	2400 (V _{f tot} 41 V)	98	0,37	105
1208	15 *	1710 (V _{f tot} 41 V)	70	0,40	105
1206	13 *	1200 (V _{f tot} 41 V)	49	0,37	105
1205	13 *	1050 (V _{f tot} 41 V)	43	0,32	105
1204	13 ^	850 (V _{f tot} 41 V)	35	0,26	105
	9 **	1350 (V _{f tot} 44 V)	59	0,93	105
	9 ^	740 (V _{f tot} 41 V)	30	0,48	105
1203	9 *	570 (V _{f tot} 41 V)	23	0,37	105
1202	6,5 ^	380 (V _{f tot} 41 V)	16	0,47	105
	6 **	675 (V _{f tot} 44 V)	30	0,90	105

^: Concerning CoB's Generation 6

*: Concerning CoB's Generation 6 and 7

**: Concerning CoB's Generation 7

The product and production sites listed on the License comply with the ENEC requirement and the UL Global Service Agreement, with reference to Terms and Conditions for the ENEC mark. The Owner of the License is entitled to use the ENEC 15 (as shown in annex 1) for the products listed on the License and manufactured at the production site listed. UL has to be informed in writing about any changes to the product or production site in accordance with the Term and Conditions of the ENEC mark.



ENEC LICENCE

Licence No. ENEC-01182-P5
Page 6/8
Date of Issue 2019-12-11

Product Key:

Variant series 3: **Fortimo SLM** zcc Lee hh s Gij a

Where:

z = CRI of LED divided by 10 (one digit, may be "7" or "8" or "9");
cc = Color temperature of LED divided by 100 (two digits, may be a value between 22 and 65);
ee = Diameter of Light Emitting Surface (LES) in mm (two digits, may be a value between 06 and 23);
hh = Holder type (two or three characters or none, may be "DL" or "PI" or "ZP" or "ZPw" or blank);
s = CoB size in mm (four digits, example 2828: CoB dimensions = 28 mm x 28 mm));
i = Number of generation of CoB (one digit, may be "6", "7");
j = Number of generation of Holder (one digit, may be "1" or "2");
a = Suffix for commercial purposes (optional)

The variant series 3 differs from the variant series 2 for different product key, for the presence of LED CoB + LED Holder and for different maximum ratings for CoB Type 1216.

Maximum ratings of the series:

CoB Type	Diameter of LES of CoB [mm]	DC Current [mA]	Power [W]	Power Density of CoB [W/mm ²]	t _c [°C]	T Holder [°C]
1216	23 *	2750 (V _{f tot} 41 V)	98	0,27	105	100
1211	18.5*	2400 (V _{f tot} 41 V)	98	0,37	105	100
1208	15 *	1710 (V _{f tot} 41 V)	70	0,40	105	100
1206	13 *	1200 (V _{f tot} 41 V)	49	0,37	105	100
1205	13 *	1050 (V _{f tot} 41 V)	43	0,32	105	100
1204	13 ^	850 (V _{f tot} 41 V)	35	0,26	105	100
	9 **	1350 (V _{f tot} 44 V)	59	0,93	105	100
	9 ^	740 (V _{f tot} 41 V)	30	0,48	105	100
1203	9 *	570 (V _{f tot} 41 V)	23	0,37	105	100
1202	6,5 ^	380 (V _{f tot} 41 V)	16	0,47	105	100
	6 **	675 (V _{f tot} 44 V)	30	0,90	105	100

^: Concerning CoB's Generation 6

*: Concerning CoB's Generation 6 and 7

**: Concerning CoB's Generation 7

The product and production sites listed on the License comply with the ENEC requirement and the UL Global Service Agreement, with reference to Terms and Conditions for the ENEC mark. The Owner of the License is entitled to use the ENEC 15 (as shown in annex 1) for the products listed on the License and manufactured at the production site listed. UL has to be informed in writing about any changes to the product or production site in accordance with the Term and Conditions of the ENEC mark.



ENEC LICENCE

Licence No. ENEC-01182-P5
Page 7/8
Date of Issue 2019-12-11

Additional information:

- The modules have been evaluated according to IEC/TR 62778 and the Lamp classification Group for Blue Light Hazard is Risk Group 1 Unlimited for modules having generation of CoB "4" or "5", Risk Group 2 for modules having generation of CoB "6", "7" when are used at maximum rated currents. These Generation 6, 7 modules are classified as Risk Group 1 if they are used according to the maximum currents listed below:

	CoB Type							
	1216	1211	1208	1205	1204	1204s	1203	1202s
Maximum Currents for RG1 Classif. [mA]	1824 (Gen 6)	1254 (Gen 6)	912 (Gen 6)	570 (Gen 6)	456 (Gen 6)	456	342 (Gen 6)	228

		CoB Type						
		1216	1211	1208	1206	1205	1204	1203
Maximum Currents for RG1 Classif. [mA]	zcc = 765	1797 (Gen 7)	1248 (Gen 7)	548 (Gen 7)	/	468 (Gen 7)	/	258 (Gen 7)
	zcc = 857	2298 (Gen 7)	1349 (Gen 7)	1040 (Gen 7)	1000 (Gen 7)	820 (Gen 7)	480 (Gen 7)	330 (Gen 7)

The product and production sites listed on the License comply with the ENEC requirement and the UL Global Service Agreement, with reference to Terms and Conditions for the ENEC mark. The Owner of the License is entitled to use the ENEC 15 (as shown in annex 1) for the products listed on the License and manufactured at the production site listed. UL has to be informed in writing about any changes to the product or production site in accordance with the Term and Conditions of the ENEC mark.



Annex 1 to License No.

ENEC-01182-P5

Annex of the form of the Mark



* Identification number of the Certification Body

Size of the mark:

The size of the mark may be reduced on the condition that it remains legible and that the ratio $b/a=1,7$ is kept

Certification Body

This is to certify that representative sample(s) of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this License, in accordance with the ENEC Requirements. The Designated License holder is entitled to use the ENEC 15 Mark (as shown in annex 1) for the Certified Product manufactured at the production site(s) identified above in accordance with the ENEC Mark Service Agreement including without limitation the ENEC Mark Testing and Certification Services Service Terms. Only those Products bearing the ENEC Mark should be considered as being covered by UL's ENEC Mark Service. This License shall remain valid unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the Date of Withdrawal of conflicting Standard(s).

