

PHILIPS

CertaDrive

Switching power supply



Datasheet

CertaDrive SPS 350W 24VDC

9290 028 89680

CertaDrive switch power supply is single output type AC/DC power supply. It uses semi-potted aluminum case which protecting rain splash and dust. This product has CQC/CB/SELV certifications which is suitable for wide applications.

Benefits

- 30,000 hours lifetime with 3 years warranty
- Design against rain splash
- Cooling by free air convection
- SELV isolation

Features

- Over voltage protection
- Short circuit protection
- Over power protection
- Over temperature protection

Application

- Area and flood lighting
- LED strip lighting

Electrical input data

Specification item	Value	Unit	Condition
Rated input voltage range	200...240	V _{ac}	Performance range
Rated input voltage	230	V _{ac}	
Rated input frequency range	50...60	Hz	Performance range
Rated input current	3.5	A	@ rated output power @ rated input voltage
Rated input power	395	W	@ rated output power @ rated input voltage
Power factor	0.65		@ rated output power @ rated input voltage
Total harmonic distortion	120	%	@ rated output power @ rated input voltage
Efficiency	89	%	@ rated output power @ rated input voltage
Input voltage AC range	180...264	V _{ac}	Safety operational range
Input frequency AC range	47...63	Hz	Safety operational range
Isolation input to output	SELV		

Electrical output data


Specification item	Value	Unit	Condition
Regulation method	Constant Voltage		
Output voltage	24	V _{dc}	
Adjustable output voltage range	21.6 ... 26.4	V _{dc}	
Output current	14.6	A	
Output voltage ripple	≤ 150	mV _{pp}	With a 0.1uF and 47uF parallel capacitor
Output power	350	W	
Line regulation	0.5	%	
Load regulation	0.5	%	
Output voltage tolerance	1	%	
Turn-on delay	≤ 1.5	s	@ rated output power @ rated input voltage
Hold-up time	≥ 20	ms	@ rated output power @ rated input voltage

Electrical data controls input

Specification item	Value	Unit	Condition
Control method	Fixed		

Wiring and Connections

Specification item	Value	Unit	Type
Input wire cross-section	0.5...3 / 12...22	mm ² / AWG	Connector HD9500, solid / stranded wire
Input wire strip length	9...10	mm	
Output wire cross-section	0.5...3 / 12...22	mm ² / AWG	Connector HD9500, solid / stranded wire
Output wire strip length	9...10	mm	




Insulation

Insulation per IEC62368-1	Input	Output	Housing/PE
Input		SELV	Basic
Output	SELV		Basic
Housing/PE	Basic	Basic	

Dimensions and weight

Specification item	Value	Unit	Tolerance (mm)
Length (A1)	219.5	mm	
Length (A2)	10.9	mm	
Length (A3)	4.9	mm	
Width (B1)	130	mm	
Width (B2)	65	mm	
Width (B3)	125	mm	
Height (C1)	48	mm	
Mounting hole diameter (D1)	8	mm	
Mounting hole diameter (D2)	4.5	mm	
Weight	870	gram	



Logistical data

Specification item	Value
Product name	CertaDrive SPS 350W 24VDC
Logistic code 12NC	9290 028 89680
Pieces per box	18

Operational temperatures and humidity

Specification item	Value	Unit	Condition
Ambient temperature	-30...+60	°C	Refer to output load derating curve
Relative humidity	20...90	%	Non-condensing

Note: 1. According to GB4943.1, the power supply is only suitable for safe use in areas below 2000 meters above sea level
2. The power supply meets EMI standards, but as part of the terminal equipment system, EMI testing needs to be carried out in the terminal equipment system

Lifetime

Specification item	Value	Unit	Condition
Driver MTBF	200,000	hours	MIL-217 method, at Ta=25°C
Driver Lifetime	30,000	hours	Measured at Ta=40°C, full load. Maximum failures = 10%

Storage temperature and humidity


Specification item	Value	Unit	Condition
Ambient temperature	-30...+85	°C	
Relative humidity	10...95	%	Non-condensing

Features

Specification item	Value		Condition
Over voltage protection	Yes		U _{out} = 27.6...32.4V. Hiccup mode, automatic recovering
Short circuit protection	Yes		Hiccup mode, automatic recovering
Over power protection	Yes		110...160%, automatic recovering
Overtemperature protection	Yes		Automatic recovering

Inrush current

Specification item	Value	Unit	Condition
Inrush current I_{peak}	90	A	Input voltage 230V
Inrush current T_{width}	1300	μs	Input voltage 230V, measured at 50% I_{peak}
Drivers / MCB 16A type B	1	pcs	Indicative value



MCB	Rating	Relative number of LED drivers
B	4A	25%
B	6A	40%
B	10A	63%
B	13A	81%
B	16A	100% (stated in datasheet)
B	20A	125%
B	25A	156%
B	32A	200%
B	40A	250%
C	4A	42%
C	6A	63%
C	10A	104%
C	13A	135%
C	16A	170%
C	20A	208%
C	25A	260%
C	32A	340%
C	40A	415%

Driver touch current / protective conductor current

Specification item	Value	Unit	Condition
Typical Protective Conductor Current (ins. Class I), output to GND	0.7	mA peak	Acc. IEC62368-1. LED module contribution not included.

Surge immunity


Specification item	Value	Unit	Condition
Mains surge immunity (diff. mode)	2	kV	L-N acc. IEC61000-4-5. 2 Ohm
Mains surge immunity (comm. mode)	4	kV	L/N-PE, acc. IEC61000-4-5. 12 Ohm

Application Info


Specification item	Value
Approval marks	CQC / CB/ SELV
Ingress Protection classification (IP)	20

Graphs


Power factor versus output power




Efficiency versus output power




THD versus output power



Output power versus input voltage



Output load derating curve



©2021 Signify Holding, IBRS 10461, 5600 VB, NL. All rights reserved.
UK importer address: Signify Commercial UK Limited, 3, Guildford Business Park, GU2 8XG.

The information provided herein is subject to change without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.
Date of release: April 16, 2021 v1

www.philips.com/oem