

# AUSTRALIAN CERTIFICATE OF SUITABILITY

<b>Certificate No.</b>	ULL-102290
<b>Page</b>	1/3
<b>Date of Issue</b>	2021-08-04
<b>Certificate Holder</b>	Signify Netherlands B.V. High Tech Campus 48, Eindhoven Netherlands 5656 AE
<b>Certified Product Description</b>	LED DRIVER
<b>Model(s)</b>	See page 2.
<b>Trade Name or Trademark</b>	PHILIPS
<b>Risk Class / Declared Class</b>	EESS OUT OF SCOPE - Non-prescribed / non-declared - Commercial (not certified for residential or household use)
<b>Certification Standard</b>	AS 61347.2.13:2018; AS/NZS 61347.1:2016+A1
<b>Certification Marking</b>	Marking shall be in accordance with the details on last page
<b>Additional Information and Conditions</b>	See Next page
<b>Expiry date</b>	2026-08-04



Stuart Foster  
Certification Officer

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)

Certification Body

This is to certify that representative samples of the Product described herein ("Certified Product") have been investigated and found in compliance with the Standard(s) indicated on this Certificate. This certificate is issued in accordance with a) the contractual agreement between UL and the certificate holder, b) the ANZ Certification Program Service Terms and c) JAS-ANZ accreditation requirements. This is NOT a Queensland Government's Recognised External Certification Scheme (RECS) certificate. It is based on type assessment of representative product(s) and is issued for use in Australia and New Zealand only.

This Certificate remains the property of UL International New Zealand Ltd.

Equipment covered by this approval must comply in all respects with the certified article, and is required to be clearly and indelibly marked with the marking indicated in the appendix to this certificate. The certificate holder must immediately notify UL International New Zealand Ltd if these conditions are not met.

Notification must be made to UL International New Zealand Ltd within 20 working days of any modification to the product, change of manufacturer or change of certificate holder details.

If the client provides copies of the certification documents to others, the documents shall be reproduced in their entirety.

This certificate shall expire on the date indicated above unless the certificate is suspended, cancelled or withdrawn for any reason prior to that date.

All dates are in Year-Month-Day format (YYYY-MM-DD).

**UL International New Zealand Ltd,**  
**54 Tarndale Grove, Albany,**  
**Auckland 0632, New Zealand.**  
**+64 9 415 3355, [customerservice.anz@ul.com](mailto:customerservice.anz@ul.com),  
**<http://newzealand.ul.com>****



# AUSTRALIAN CERTIFICATE OF SUITABILITY – APPENDIX

**Certificate No.** ULL-102290  
**Page** 2/3  
**Date of Issue** 2021-08-04

## Model Rating Information:

Xi LP 100W 0.3-1.05A S1 230V I155,  
Xi LP 100W 0.3-1.05A S1 230V I155CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 0.53-0.45 A; PF: 0.95;  
Iout: 0.3-1.05 A; Uout: 46-143 V; Uout(Max.open circuit): 220 Vdc;  
Pout: 100 W; tc: 80 °C; ta: -40...+55 °C; IP67; independent

Xi LP 100W 0.5-1.5A S1 230V I155,  
Xi LP 100W 0.5-1.5A S1 230V I155CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 0.53-0.45 A; PF: 0.95;  
Iout: 0.5-1.5 A; Uout: 33-95 V; Uout(Max.open circuit): 150 Vdc;  
Pout: 100 W; tc: 80 °C; ta: -40...+55 °C; IP67; independent

Xi LP 150W 0.3-1.05A S1 230V I175,  
Xi LP 150W 0.3-1.05A S1 230V I175CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 0.85-0.65 A; PF: 0.95;  
Iout: 0.3-1.05 A; Uout: 71-214 V; Uout(Max.open circuit): 320 Vdc;  
Pout: 150 W; tc: 85 °C; ta: -40...+50 °C; IP67; independent

Xi LP 150W 0.5-1.5A S1 230V I175,  
Xi LP 150W 0.5-1.5A S1 230V I175CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 0.85-0.65 A; PF: 0.95;  
Iout: 0.5-1.5 A; Uout: 50-143 V; Uout(Max.open circuit): 220 Vdc;  
Pout: 150 W; tc: 85 °C; ta: -40...+50 °C; IP67; independent

Xi LP 200W 0.3-1.05A S1 230V I195,  
Xi LP 200W 0.3-1.05A S1 230V I195CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 1.0-0.9 A; PF: 0.95;  
Iout: 0.3-1.05 A; Uout: 142-286 V; Uout(Max.open circuit): 420 Vdc;  
Pout: 200 W; tc: 85 °C; ta: -40...+55 °C; IP67; independent

Xi LP 200W 0.5-1.5A S1 230V I195,  
Xi LP 200W 0.5-1.5A S1 230V I195CF:  
Uin: 220-240 VAC; fn: 50/60 Hz; lin: 1.0-0.9 A; PF: 0.95;  
Iout: 0.5-1.5 A; Uout: 100-200 V; Uout(Max.open circuit): 300 Vdc;  
Pout: 200 W; tc: 85 °C; ta: -40...+55 °C; IP67; independent

## Additional Information:

For NON-IC LED drivers :

The requirements of EESS General Guidance Notice 20-007 for NON-IC classified LED drivers is applicable.  
Refer <https://www.eess.gov.au/news-and-notifications/information-and-advisory-notes> for more information.

Certification Body

**UL International New Zealand Ltd,**  
54 Tarndale Grove, Albany,  
Auckland 0632, New Zealand.  
+64 9 415 3355, [customerservice.anz@ul.com](mailto:customerservice.anz@ul.com),  
<http://newzealand.ul.com>



# AUSTRALIAN CERTIFICATE OF SUITABILITY - MARKING

**Certificate No.** ULL-102290  
**Page** 3/3  
**Date of Issue** 2021-08-04

Certified products may be marked with:

- A) the Regulatory Compliance Mark (RCM), in which case all the requirements of all relevant parts of AS/NZS 4417 applicable to the article shall be fulfilled.



and/or;

- B) The product certification number as follows (minimum size is not specified, as long as the Certification Number is legible).

ULL-102290

Certification Body

UL International New Zealand Ltd,  
54 Tarndale Grove, Albany,  
Auckland 0632, New Zealand.  
+64 9 415 3355, [customerservice.anz@ul.com](mailto:customerservice.anz@ul.com),  
<http://newzealand.ul.com>

