



中国国家强制性产品认证证书

证书编号: 2020011002339616

委托人名称、地址

昕诺飞(中国)投资有限公司
上海市闵行区田林路 888 弄 9 号楼

生产者(制造商)名称、地址

昕诺飞(中国)投资有限公司
上海市闵行区田林路 888 弄 9 号楼

生产企业名称、地址

产品名称和系列、规格、型号

LED 模块用交流电子控制装置(LED 控制装置, 独立式, 恒流模式, 自耦式,
ta:55°C/60°C, tc:80°C/85°C, I 类, IP67, 适宜直接安装在普通可燃材料表
面, 控制端口调光+非控制端口调光)

见附件。110-277V~, 50/60Hz

产品标准和技术要求

GB 17625.1-2012; GB/T 17743-2017; GB 19510.1-2009; GB
19510.14-2009

上述产品符合强制性产品认证实施规则 CNCA-C10-01:2014 的要求,
特发此证。

发证日期: 2020 年 11 月 13 日 有效期至: 2025 年 11 月 13 日
证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书的相关信息可通过国家认监委网站 www.cnca.gov.cn 查询

经中国合格评定国家认可委员会认可 CNAS C001-P



主任:

陆楠

中国质量认证中心



中国国家强制性产品认证证书

附 录

第 1 页 共 1 页

证书编号: 2020011002339616

纸 号:

序号	型号	输出电流 (A)	输出电压 (Vdc)	最大输出电 压 (Vdc Max)	输出功 率 (W)	ta (°C) tc (°C)
1	Xi LP 100W 0.3-1.05A S1 GL I175	0.3-1.05	46-143	220	100	Uin:110-240Vac 时: ta: 55°C, tc: 80°C; Uin:240-277Vac 时: ta: 60°C, tc: 80°C
2	Xi LP 100W 0.5-1.5A S1 GL I175	0.5-1.5	33-95	150	100	Uin:110-240Vac 时: ta: 55°C, tc: 80°C; Uin:240-277Vac 时: ta: 60°C, tc: 80°C
3	Xi LP 150W 0.3-1.05A S1 GL I200	0.3-1.05	71-214	320	150	Uin:110-240Vac 时: ta: 55°C, tc: 85°C; Uin:240-277Vac 时: ta: 60°C, tc: 85°C
4	Xi LP 150W 0.5-1.5A S1 GL I200	0.5-1.5	50-143	220	150	Uin:110-240Vac 时: ta: 55°C, tc: 85°C; Uin:240-277Vac 时: ta: 60°C, tc: 85°C

输入均为: 110-277V~, 50/60Hz。

注: 此附录与证书同时使用时有效。



主 任:

陆 楠

中国质量认证中心



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2020011002339616

NAME AND ADDRESS OF THE APPLICANT

Signify (China) Investment Co., Ltd.

Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China

NAME AND ADDRESS OF THE MANUFACTURER

Signify (China) Investment Co., Ltd.

Building no.9, Lane 888, Tianlin Road, Minhang District, Shanghai 200233, China

NAME AND ADDRESS OF THE FACTORY

PRODUCT NAME, MODEL AND SPECIFICATION

A.C. Supplied Electronic Controlgear For LED Modules (Independent , Constant Current Mode, Auto-wound Controlgear, ta:55°C/60°C , tc:80°C/85°C , Class I, IP67, Suitable For Direct Mounting On Normally Flammable Material, Controlled Port Dimming+Non-Controlled Port Dimming)

See Appendix. 110-277V~, 50/60Hz

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2012;GB/T 17743-2017;GB 19510.1-2009;GB 19510.14-2009

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO.CNCA-C10-01:2014).

Valid from: Nov.13,2020

Valid until: Nov.13,2025

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through CNCA's website: www.cnca.gov.cn

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



President:

Lu Mei

CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

APPENDIX

Page 1 of 1

CERTIFICATE NO.: 2020011002339616

PAPER:

序号	型号	输出电流 (A)	输出电压 (Vdc)	最大输出电 压 (Vdc Max)	输出功 率 (W)	ta (°C) tc (°C)
1	Xi LP 100W 0.3-1.05A S1 GL I175	0.3-1.05	46-143	220	100	Uin:110-240Vac 时: ta: 55°C, tc: 80°C; Uin:240-277Vac 时: ta: 60°C, tc: 80°C
2	Xi LP 100W 0.5-1.5A S1 GL I175	0.5-1.5	33-95	150	100	Uin:110-240Vac 时: ta: 55°C, tc: 80°C; Uin:240-277Vac 时: ta: 60°C, tc: 80°C
3	Xi LP 150W 0.3-1.05A S1 GL I200	0.3-1.05	71-214	320	150	Uin:110-240Vac 时: ta: 55°C, tc: 85°C; Uin:240-277Vac 时: ta: 60°C, tc: 85°C
4	Xi LP 150W 0.5-1.5A S1 GL I200	0.5-1.5	50-143	220	150	Uin:110-240Vac 时: ta: 55°C, tc: 85°C; Uin:240-277Vac 时: ta: 60°C, tc: 85°C

输入均为: 110-277V~, 50/60Hz。

NOTE: This appendix forms a part of the certificate for china compulsory product certification, and must be used together with the certification.



President:

Lu Mei

CHINA QUALITY CERTIFICATION CENTRE