



A P P R O V A L S ®

Certificate of Suitability

Certificate No.: SAA200649

Certificate Holder: Signify Netherlands B.V.
High Tech Campus 48,
5656 AE Eindhoven,
Netherlands

Regulatory Definition: Non-Prescribed
Product Description: LED Driver (Built-in, Auto wound, Non-SELV)
Trade Name: PHILIPS
Model No.: Xitanium 35W 0.08-0.35A 220V 21 230V
Markings: Uin: 220-240Vac; 50/60Hz; or 186-250Vdc;
PF: 0.9C; Iin: 0.18 Aac, 0.21-0.16 Adc;
Pin: 39W; PF: 0.9C;

Standard: Uout: 50-220 Vdc, 250Vdc(max.);
Iout: 0.08-0.35Adc; Pout: 35W
ta: -20 to +50°C tc:75°C

Conditions: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1
All models approved under this Certificate
must comply with the Standard requirements
of the end product when installed.

Certification Mark: RCM and SAA200649

Date First Registered: 14 April 2020
Date of Expiry: 14 April 2025

R.A. Hill

For and on Behalf of
SAA Approvals Pty Ltd


SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 and declared a RECS under *Qld Electrical Safety Act 2002 and Electrical Safety Regulations 2013* certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



Issued: 14-04-20 200649/1

www.jas-anz.org/register



A P P R O V A L S ®

Certificate of Suitability

Addendum

Certificate No.: SAA200649

Date of Issue: 14 April 2020

Regulatory Definition: Non-Prescribed

Product Description: LED Driver (Built-in, Auto wound, Non-SELV)

Additional Models	Trade Name	Rating
Xitanium 60W 0.08-0.35A 300V 21 230V	PHILIPS	Uin: 220-240Vac; 50/60Hz; or 186-250Vdc; PF: 0.9C; Iin: 0.3 Aac, 0.36-0.27 Adc; Pin: 66W; PF: 0.9C; Uout: 100-300 Vdc, 330Vdc(max.); Iout: 0.08-0.35Adc; Pout: 60W
Xitanium 60W 0.15-0.5A 220V 21 230V	PHILIPS	Uin: 220-240Vac; 50/60Hz; or 186-250Vdc; PF: 0.9C; Iin: 0.31 Aac, 0.36-0.27 Adc; Pin: 67W; PF: 0.9C; Uout: 50-220Vdc, 250Vdc(max.); Iout: 0.15-0.5Adc; Pout: 60W
Xitanium 90W 0.25-0.7A 220V 21 230V	PHILIPS	Uin: 220-240Vac; 50/60Hz; or 186-250Vdc; PF: 0.9C; Iin: 0.45 Aac, 0.53-0.39 Adc; Pin: 97W; PF: 0.9C; Uout: 50-220 Vdc, 250Vdc(max.); Iout: 0.25-0.7Adc; Pout: 90W

R.A. Hill

For and on Behalf of
SAA Approvals Pty Ltd


SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 and declared a RECS under *Qld Electrical Safety Act 2002 and Electrical Safety Regulations 2013* certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 14-04-20 200649/2