


Output Power (W)	Output Voltage (V)	Output Current (A)	Efficiency at Max Load	Max Case Temp (°C)	Input Current (Arms)	Max Input Power (W)	Inrush Current (Apk/50%-µs)	THD @ Max Load (%)	Power Factor @Max Load	Surge Protection Com/Diff(KV)	Weight (Kg)	Envir. Protection Rating
100	58-96	1.05	@ 240V	80	@ 240V	110	@ 240V	<10 @Max	> 0.95	4 / 4	0.7	Damp
			90%		0.45		278/400	Load				



PHILIPS

Ordering 12NC	92900 2104706
Brand Name	Xitanium
Description	Xitanium 100W 1.05A 1-10V Dim PLS
Model Number	X100C105V096CNY1AO
Input Voltage	240V
Input Frequency	50 / 60 Hz
RoHS	Yes
Approbations	IS 15885 (Part 2 / Sec 13)
Status	BIS Certification under process

120V to 277V

PHILIPS

LED Electronic Driver

Model No: X100C105V096CNY1AO

Dry & Damp
location

RoHS
COMPLIANT

XITANIUM™

100W 1.05A
0-10V DIMMING

Uin	240Vac
Freq	50Hz
Iin	0.45Aac
PF	0.95
Uout	58 - 96Vdc
Iout	1.05Adc
ta	-20...+55°C
Uout (max. open circuit) <180Vdc	

Input Over Voltage Protection

Product Data	
Full product code	9290 021 04706
Full product name	Xitanium 100W 1.05A 1-10V Dim PLS
Net weight per piece	700 gms
Dimming	Yes(0-10V dimming)
Ambient Temp. Range	-20°C to +55°C
Corresponding T case	+5°C to +80°C
Line Voltage (AC operation)	120 - 277V +/-10%
Line Voltage (Performance)	240V +/-15%, CLO @ 120V-277V
Line Current	0.45A @ 240V
Line Frequency	50/60 Hz
Envir. Protection Rating	Dry and Damp
Life at Tc 80 dgree C	50000 hrs (nom.)
Suitable For Outdoor Use	Yes
Max. Tc	80°C
Inrush Current	278 Apk @ 240V
Max. Driver number on MCB 16A (Type B)	11 (max.)
Input Over Voltage	Can Survive input Voltage Stress of 320V for 48 hours
Input Over Voltage Cut Off	Auto Shutdown at ≥ 325V and Auto Recovery at 300V - 315V
Input Over Voltage Protection	Can Survive input Voltage Stress of 440V for 8 hours
Input Under Voltage Protection	Can Survive input Voltage Stress of 100V for 48 hours
LED Current Tolerance	±5%
Earth Leakage Current	0.7 mA (max)
Output Current Ripple	10% at 1.05A (ripple = pk / avg.) for frequency 50 - 1K Hz
Generated disturbances and EMI	EN 55015/CISPR15
	Conducted EMI, 9kHz-30MHz
THD Total	≤ 10% @ Full Load @ 240V Supply
P.F. at Max. Load	≥ 0.95
Wire Isolation	All Wires are double isolated to Ground
Protection	Short Circuit and Open Circuit Protection for LED + and LED -



Ordering 12NC	92900 2104706
Brand Name	Xitanium
Description	Xitanium 100W 1.05A 1-10V Dim PLS
Model Number	X100C105V096CNY1AO
Input Voltage	240V
Input Frequency	50 / 60 Hz
RoHS	Yes
Approbations	IS 15885 (Part 2 / Sec 13)
Status	BIS Certification under process

Installation & Application Notes :

Section I - Physical Characteristics

- 1.1 LED Driver shall be installed inside an electrical enclosure
- 1.2 Wiring inside electrical enclosure shall comply with 600V/105°C rating or higher

Section II - Performance

- 2.1 LED Driver has a rated lifetime of 50,000 hours @ $T_c \leq 80^\circ\text{C}$
- 2.2 LED Driver tolerates sustained open circuit and short circuit output conditions without damage
- 2.3 LED Driver maximum allowable case temperature is 80°C - see product label for measurement location
- 2.4 LED Driver has Thermal Fold Back or shutdown above T_{cmax} , please refer to the table for typical performance
- 2.5 LED Driver reduces output power to LEDs if its case temperature $> 85^\circ\text{C}$
- 2.6 LED Driver complies with the requirements of IS 15885 (Part 2 / Sec 13)

ELECTRICAL RATINGS :

Model	Input, 50/60 Hz		Output (nominal)		
	V	A	V DC	mA DC Max	Watts
Xitanium 100W 1.05A 1-10V Dim PLS	240	0.45	96	1050	100

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVES USE) :

Section III - Conditions of acceptability

When installed in the end-use equipment, the following are among the considerations to be made :

- 3.1 The equipment shall be installed in compliance with the enclosure, mounting, spacing, casualty and segregation requirements of the ultimate application.
- 3.2 The driver case must be grounded in the end-use application.
- 3.3 The driver is suitable for use in "Damp" and "Dry" locations.
- 3.4 When the drivers are installed in the end-use application, the case temperature should not exceed the temperature limits specified in the following table:


Model	Input Voltage, Hz	Max Case @ T_c , $^\circ\text{C}$
Xitanium 100W 1.05A 1-10V Dim PLS	240 , 50/60	80

- 3.5 The leakage current test should be repeated in the end device.


Model	Input Voltage, Hz	Leakage Current
Xitanium 100W 1.05A 1-10V Dim PLS	240 , 50/60	0.7mA max.



Ordering 12NC	92900 2104706
Brand Name	Xitanium
Description	Xitanium 100W 1.05A 1-10V Dim PLS
Model Number	X100C105V096CNY1AO
Input Voltage	240V
Input Frequency	50 / 60 Hz
RoHS	Yes
Approbations	IS 15885 (Part 2 / Sec 13)
Status	BIS Certification under process




Inrush Current info :



Vin	Ipeak	T (@50% of Ipeak)
240 Vrms	278A	400 μ s

Lifetime vs Tcase of Driver :



Failure rate info based upon field called rate data:
< 0.2% per 1 Khr @ $\leq T_{case}$ 80°C

Revised 04/03/2019



Ordering 12NC	92900 2104706
Brand Name	Xitanium
Description	Xitanium 100W 1.05A 1-10V Dim PLS
Model Number	X100C105V096CNY1AO
Input Voltage	240V
Input Frequency	50 / 60 Hz
RoHS	Yes
Approbations	IS 15885 (Part 2 / Sec 13)
Status	BIS Certification under process


Electrical Specifications

All the specifications are typical and at 25°C Tcase unless specified otherwise.

0-10V Dimming Curve

Dimming source current from the driver: 150µA (@ 0<Vdim<8V)

Minimum dim level: 10% of Iout



Isolation :

Isolation	Input Wires	Output Wires	Chassis
Input Wires	NA	1750 V	3750 V
Output Wires	1750 V	NA	3750 V
Chassis	3750 V	3750 V	NA